



## CC-2

### 2-channel stereo amplifier

CC-2 is a small and powerful amplifier with a RMS power output of 2 x 170 Watts. In 4 ohm mono bridge-connection, it puts out all of 340 Watts.

- Built-in low-pass filter for subwoofers, variable between 50 and 500 Hz.
- The high-pass filter is also variable between 50 and 500 Hz.
- Built-in protection circuits shut down the amplifier in the event of overloads.
- High level input with AUTO-start function
- Bass EQ variabel from 0 till +6dB.
- THD at 5W, 1 kHz: <0,02%
- Damping factor: >150
- Signal to noise ratio, A-weighted: 110 dB



### Specifications

	<b>CC-2</b>
Number of channels	2
Amplifier class	AB
Power output RMS in 4 ohm	2 x 110 W
Power output RMS in 2 ohm	2 x 170 W
Power output RMS 4 ohm bridged	1 x 340 W
Signal to noise ratio, A-weighted	110 dB
Damping factor	>150
THD @ 5 W, 1 kHz	< 0,02%
Frequency response	10 Hz - 50 k
Input impedance, low level	6 kohm
Input sensitivity	1 - 4V
Input impedance, high level	45 ohm
High level input	Yes
Filter high-pass adjustable	50 - 500 Hz*
Filter low pass adjustable	50-500 Hz*
can be switched in/out	
Bass EQ @ 60 Hz	0 - +6 dB
Power consumption, idle	0,5 A
Power consumption, max	43A
Fuse	2 x 20 A
Dimensions HxWxD(mm)	51 x 129 x 260
Dimensions (inch)	2 x 5,07 x 10,2
Weight	1,87 kg



*Sound tuned in England*

DLS Sweden  
[www.dls.se](http://www.dls.se)  
E-mail. [info@dls.se](mailto:info@dls.se)